

800-638-0801

MagneLink inc.

Heavy Duty Magnetic Switch for DC Voltage

APPLICATIONS

Compactor Equipment
Baler Equipment
Truck or Trailer Doors
Rugged Environments

MAGNETIC SWITCH ADVANTAGE:

Not prone to being over-riden
by tape, mechanical
intervention, dirt, or ice.

GENERAL

SPECIFICATIONS

HOUSING: Glass-Filled Nylon

MAGNET: 1000 Gauss

CABLE: 18 AWG with UL PVC
jacket

OPERATING

TEMPERATURE:

14°F - 140°F (-10°C - 60°C)

SHOCK RESISTANCE: 50g

VIBRATION RESISTANCE:

30g

ENVIRONMENT: Suitable for
use in class 1, 3R & 4
applications

ACTIVATION DISTANCE: 0.5
inch minimum, release 1.5
inch maximum

MLP Housing



- Robust design to extend the life of the switch and allow for maximum reliability.
- Employs a Transistor semiconductor in conjunction with a reed to carry higher DC loads.
- Housing made of Glass-Filled Nylon material. Well suited for rugged environments.
- UL/CSA Recognized

SPECIFICATIONS:

Part Number	Contact Style	Operating Voltage (V)	Operating Current (A)	# of Leads
MLP-Txx ¹	SPST/ Normally Open	100 DC	2	2
MLP-Xxx ¹	SPST/ Normally Closed	100 DC	2	2
MLP-Yxx ¹	SPDT	100 DC	2	3

'xx' indicates cable length in feet

Note 1: UL/ CSA recognized

ORDERING OPTIONS:

Contact factory for availability of custom requirements.